

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problems Mailbox.**

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : B81B 3/00, B41J 2/045	A1	(11) International Publication Number: WO 00/64805 (43) International Publication Date: 2 November 2000 (02.11.00)
(21) International Application Number: PCT/AU00/00341 (22) International Filing Date: 20 April 2000 (20.04.00) (30) Priority Data: PP 9930 22 April 1999 (22.04.99) AU (71) Applicant (for all designated States except US): SILVERBROOK RESEARCH PTY. LTD. [AU/AU]; 393 Darling Street, P.O. Box 207, Balmain, New South Wales 2041 (AU). (72) Inventors; and (75) Inventors/Applicants (for US only): SILVERBROOK, Kia [AU/AU]; (AU). MCAVOY, Gregory, John [IE/AU]; Silverbrook Research Pty Ltd, 393 Darling Street, Balmain, New South Wales 2041 (AU). (74) Agent: SILVERBROOK, Kia; Silverbrook Research Pty Ltd, 393 Darling Street, Balmain, New South Wales 2041 (AU).		(81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report.
(54) Title: ACTUATOR ELEMENT (57) Abstract An actuator element for a micro electromechanical device comprises a movable arm formed at least in part from a titanium-aluminium nitride composition. This composition has a relatively high oxidation temperature, thus allowing a high temperature to be generated in the actuator element over a short period of time. In one embodiment, the actuator element forms part of a thermal bend actuator in an ink jet device.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

ACTUATOR ELEMENT

Field of the Invention

5 This invention relates to an actuator element which forms a portion of a micro electro-mechanical device. The invention is herein described in the context of an ink jet printer but it will be appreciated that the application does have application to other micro electro-mechanical devices such as micro electro-mechanical pumps.

Background of the Invention

10 Micro electro-mechanical devices are becoming increasingly well known and normally are constructed by the employment of semi-conductor fabrication techniques. For a review of micro-mechanical devices consideration may be given to the article "The Broad Sweep of Integrated Micro Systems" by S. Tom Picraux and Paul J. McWhorter published December 1998 in IEEE Spectrum at pages 24 to 33.

15 One type of micro electro-mechanical device is the ink jet printing device from which ink is ejected by way of an ink ejection nozzle chamber. Many forms of the ink jet printing device are known. For a survey of the field, reference is made to an article by J Moore, "Non-Impact Printing: Introduction and Historical Perspective", Output Hard Copy Devices, Editors R Dubeck and S Sherr, pages 207 - 220 (1988).

20 A new form of ink jet printing has recently been developed by the present applicant, this being referred to as Micro Electro Mechanical Inkjet (MEMJET) technology. In one embodiment of the MEMJET technology, ink is ejected from an ink ejection nozzle chamber by a paddle or plunger which is moved toward an ejection nozzle of the chamber by an electro-mechanical actuator for ejecting drops of ink from
25 the ejection nozzle chamber.

The present invention relates to an actuator element for use as an integrated component in the MEMJET technology and in other micro electro-mechanical devices.

Summary of the Invention

30 The invention may be broadly defined as providing an actuator element as a portion of a micro electro-mechanical device, wherein the actuator element comprises a

movable arm that is connected at one end to a substrate and which is formed at least in part from a titanium-aluminium nitride composition. The aluminium preferably is present in an amount not greater than 55% of the total titanium-aluminium composition and most preferably is present in an amount equal to about 20% of the total titanium-aluminium composition.

The movable arm of the actuator element preferably is formed by a sputter process as one step in a semi-conductor structure fabrication process. More specifically, the movable arm of the actuator element may be formed by reactively sputtering material from a titanium-aluminium alloy in the presence of nitrogen gas.

Detailed Description of the Invention

The actuator element of the present invention in its preferred form is fabricated as a part of a printhead ink ejector from which ink is ejected by actuation of a thermal actuator. The thermal actuator includes first and second arms which are interconnected in a manner such that they are caused to bend when electrical current is passed through the first arm, causing the first arm to be heated and to expand relative to the second arm.

The first and second arms are coupled to a movable element such as a paddle within an ink ejector nozzle, and bending of the arms causes displacement of the movable element and consequential ejection of ink from the nozzle.

For a more detailed description of the above arrangement, reference may be made to International Patent Application No. PCT/AU00/00095 filed on February 11, 2000 lodged by the present applicant.

Titanium nitride has been proposed as a material that might be suitable for use in forming the arm through which the electric (heating) current is passed. That material is known to be suitable for use in the fabrication of semi-conductor devices and it possesses a coefficient of thermal expansion that is in the order required to produce desired bending characteristics.

However, it has been determined that, in order to maximise printer operating efficiency, a high temperature should be generated in the thermal actuator over a short period of time, typically less than 2 micro seconds, and this imposes a limit on the use

of titanium nitride. Titanium nitride is known to oxidise at a temperature of around 600°C and this imposes a constraint on the use of that material.

It is in this context that the titanium-aluminium nitride composition has been found to be suitable, having as it does an oxidation temperature in the order of 900°C.

The Claims:

1. An actuator element forming a portion of a micro electro-mechanical device
and which comprises a movable arm that is connected at one end to a substrate
5 and which is formed at least in part from a titanium-aluminium nitride
composition.
2. The actuator element as claimed in claim 1 wherein the composition contains
aluminium in an amount not greater than 55% of the total titanium-aluminium
composition.
- 10 3. The actuator element as claimed in claim 1 wherein the aluminium is present in
the composition in an amount equal to about 20% of the total titanium-
aluminium composition.
4. The actuator element as claimed in claim 1 when formed by reactively
sputtering material from a titanium-aluminium alloy in the presence of nitrogen
15 gas.

INTERNATIONAL SEARCH REPORT

International application No.
PCT/AU00/00341

A. CLASSIFICATION OF SUBJECT MATTER

Int. Cl. ⁷: B81B 3/00, B41J 2/045

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC: B41J, B81B, B81C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
DWPI, JAPIO

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 690329 A (TEXAS INSTRUMENTS INCORPORATED) 3 January 1996 Whole document	1-4

☐ Further documents are listed in the continuation of Box C ☒ See patent family annex

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance
 "E" earlier application or patent but published on or after the international filing date
 "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
 "O" document referring to an oral disclosure, use, exhibition or other means
 "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
 "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
 "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
 "&" document member of the same patent family

Date of the actual completion of the international search
18 May 2000

Date of mailing of the international search report

Name and mailing address of the ISA/AU

AUSTRALIAN PATENT OFFICE
PO BOX 200, WODEN ACT 2606, AUSTRALIA
E-mail address: pct@ipaustrialia.gov.au
Facsimile No. (02) 6285 3929

Authorized officer

13 JUN 2000
MICHAEL HALL
Telephone No : (02) 6283 2474

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.
PCT/AU00/00341

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report				Patent Family Member			
EP	690329	CA	2149931	CN	1117108	JP	8054555
		US	5652671				
							END OF ANNEX